Wedderburn®
Since 1896.

Industrial Thermal Label Printer

Model : WTPTI2612T

WTPTI2612T Industrial thermal label printer designed and built for high volume industrial label printing. Featuring 6.6 inch (168 mm) print width, high print speeds of up to 12 inches (305 mm) per second, heavy duty die cast aluminium design, large 450 m ribbon capacity and, colour LCD screen with 6 button menus along with touch panel operation and range of interface options.

FEATURES — WTPTI2612T

- thermal direct or thermal transfer label printing
- 203 dpi print resolution
- up to 12 inches (305 mm) per second print speed
- 6.6 inch (168 mm) maximum print width
- 4.3" Colour LCD touch screen
- SD Flash memory card ready for 32GB memory expansion
- heavy duty die-cast aluminium design
- 450 m ribbon capacity, O.D 80 mm and 1" core (inside or outside)
- ribbon width 51 mm – 178 mm
- RS232, USB, Centronics and Ethernet Interface
- USB host for scanner or PC keyboard
- compatible with EPL, ZPL and ZPLII printer languages
- gap transmissive sensor (position adjustable)
- black mark reflective sensor (position adjustable)
- compatible for use with continuous, die-cut, fan-fold, tag, notched, black mark (outside wound) media types
- media width 51 mm – 172 mm
- media core diameter 76.2 mm (3") only
- media roll O.D. max 208 mm (based on a 25.4 mm core)
- label length 10 - 14,732 mm
- includes Bartender Ultralite label design software compatible with Microsoft Windows (not compatible with MAC OS)

SPECIFICATIONS

Dimensions (mm):	355 (W) x 520 (D) x 337 (H)
Net weight:	23 kg



Specifications may change without notice

Phone: 1300 970 111 **enquiries@wedderburn.com.au** **www.wedderburn.com.au**